

TK-3230DX



Portable UHF Business Two-Way Radio
TK-3230DX

[+ Zoom](#)



Compact, Lightweight Design & Operating Ease

Compact enough to carry anywhere with ease, the TK-3230DX has a distinctively ergonomic form that's handy to hold and operate. It weighs a mere 5.5 oz (155 g) with the rechargeable Li-ion battery and control buttons, which are simple to use with PTT, MON, MENU, CAL, UP and DOWN operations.

1.5 Watts Transmit Power & Range of up to 5 Miles

The TK-3230DX offers 1.5 watts of power to enable direct radio-to-radio communication on the same frequency (simplex) for up to 5 miles.

Talk Range	
Open areas without obstructions	Up to 5 miles (8 km)

Residential areas (near buildings)	Up to 1.5 miles (2.4 km)
In steel and/or concrete reinforced buildings	Up to 225,000 sq. ft (20,900 sq. m)
In high-rise buildings	Up to 17 floors

Note: Talk range will vary based on terrain and conditions.

All-in-One Package

The TK-3230DX is ready for use immediately after purchase. It comes with essential accessories including a fast charger, 2,000 mAh Li-ion battery and a belt clip.

Battery life (When used for 5% transmit, 5% receive, and 90% standby)	18 hours with saver on
	14 hours with saver off
Battery charging time	2.5 hours

Modifiable 6 Preset Channels From 99 Pre-Stored Frequencies

Users can modify each of 6 preset channels to any of the 99 pre-stored frequencies.

39-QT/168-DQT Coded Squelch

Sub-audible QT tone & DQT digital codes mute undesired voice traffic audio and segregate user groups on shared frequencies or radio system. The user can pick any of the pre-stored channel settings.

Compatibility

The ability to choose frequency and QT/DQT channel settings allows the ProTalk® to operate on the same channels and coded squelch tones as other UHF business radio brands. So choosing the KENWOOD ProTalk® XLS will not impact on any of your previous investments in radio equipment.

SELCALL – FleetSync® PTT ID and Caller ID Display

KENWOOD's FleetSync digital signaling system includes PTT ID digital Alphanumeric Number Identification (ANI) for instant radio call identification. FleetSync also includes caller ID display and selective calling (Individual call, Group call and Broadcast call). Users can also set the alert tone (1-10, Off) for Individual call and Group/Broadcast call.

4-digit 7-segment LCD with Backlighting

The large 4-digit 7-segment display makes it easy to check on both channel and signaling information. There is also a 3-level icon in the LCD to indicate how much battery power is left.



Selectable Power on Tone

The radio is set to output a tone when the power is turned on. The user can select from 3 selection tones.

Channel Scan

Channel scanning can be used to monitor multiple channels without searching manually.

OTHER FEATURES

- MIL-STD 810 C, D, E, F and G (refer to the chart on the right)
- Built-in VOX
- Built-in Privacy Talk
- Key Lock/Super Lock
- Compander
- Battery Saver
- 10-call Alert Tone
- Busy Channel Lockout