

The Next Generation of the IC-V80, with 7 W Output Power and 1500 mW Audio



7 W output power plus new antenna provides 1.5 times* more communication distance

* Wide open space. Approximate, comparing the IC-V86 with the IC-V80. Communication range may differ depending on operating environment or weather conditions, etc. 7 W output power is only for the IC-V86.

1500 mW powerful audio and 1.5 times* higher sound pressure

* Approximate, comparing the IC-V86 with the IC-V80.

Dust-protection, water resistance and a tough body (IP54 and MIL-STD 810G)

19 hours* of long lasting battery life

* EX Hi power with BP-298. TX : RX : standby = 5 : 5 : 90 (3 sec. : 3 sec. : 54 sec.) (The Power Save function is set to "P-S.16")

No PC programming necessary, settings changeable from the radio*

* PC programming is also available.


Durable BNC type antenna connector

Made in Japan quality and reliability

And More

- Audio volume/VFO mode/Memory channel mode can be changed with the rotary knob
- Supplied BC-240, battery charger with a charging control function that prolongs the life of the battery
- Integrated VOX function
- 200 memory channels, 1 Call channel and 6 scan edges
- Built-in CTCSS and DTCS encoder/decoder
- Priority, program, memory, skip and tone scanning

Communication distance comparison



* Wide open space



SPECIFICATIONS

GENERAL	IC-V86	IC-U86
Frequency range (TX/RX guaranteed range)	136–174 MHz (EX Hi power TX : 144–160 MHz)	EXP1 : 400–472 MHz (EX Hi power TX : 430–450 MHz) EXP2 : 330–400 MHz (EX Hi power TX : 335.4–380 MHz)
Type of emissions	F2D, F3E (FM, FM-N)	
Number of channels	207 channels (200 memory channels, 1 call channel and 6 scan edges)	
Antenna impedance	50 Ω	
Power supply requirement	7.5 V DC	
Operating temperature range	–20 °C to +60 °C, –4 °F to +140 °F	
Frequency stability	±2.5 ppm (–20 °C to +60 °C, –4 °F to +140 °F)	
Current drain TX (EX Hi/Mid/Low)	1.6/1.4/1.0/0.5 A typical	EXP1: 1.6/1.5/1.0/0.5 A typ. EXP2: 1.6/1.4/0.9/0.5 A typ.
RX (Max. audio)	450 mA typ. (INT SP), 200 mA typ. (EXT SP)	450 mA typ. (INT SP), 200 mA typ. (EXT SP)
Dimensions (W×H×D) (Projections not included)	58.6 × 112 × 30.5 mm, 2.3 × 4.4 × 1.2 in (with BP-298)	
Weight (Approximate)	300 g, 10.6 oz (with BP-298, FA-B57V)	290 g, 10.2 oz (with BP-298, FA-B57U)
TRANSMITTER		
Output power (EX Hi/Hi/Mid/Low)	7.0/5.5/2.5/0.5 W	5.5/4.2/0.5 W
Maximum frequency deviation	±5.0 kHz/±2.5 kHz (Wide/Narrow)	
Spurious emissions	Less than –60 dB	
External microphone connector	3-conductor 2.5 (d) mm (1/10")/2.2 kΩ	
RECEIVER		
Sensitivity	–124 dBm typical	EXP1: –121 dBm typical EXP2: –123 dBm typical
Squelch sensitivity	–126 dBm typical	EXP1: –123 dBm typical EXP2: –125 dBm typical
Selectivity (Wide/Narrow)	75 dB typical/70 dB typical	70 dB typical/68 dB typical
Intermodulation	65 dB typical	
Audio output power Internal speaker External speaker	1500 mW typical (with 8 Ω load) 550 mW typical (with 8 Ω load)	
External speaker connector	3-conductor 3.5 (d) mm (1/8")/ 8 Ω	

All stated specifications are subject to change without notice or obligation.

Applicable U.S. Military Specifications & IP Rating

Standard	MIL 810G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Rain Blowing/Drip	506.5	I, III
Humidity	507.5	II
Salt Fog	509.5	–
Dust Blowing	510.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

Ingress Protection Standard

Dust and Water	IP54 (Dust-protection, water resistance)
----------------	--

Supplied accessories : (* May differ, depending on transceiver version)

- BP-298/BP-264, battery pack* ● BC-240, Desktop charger ● BC-242, AC adapter
- MB-124, belt clip ● Antenna*

Countermeasures against Counterfeit Products

The "3D GENUINE Icom label" and "QR Code Genuineness Determination System" are attached for proof of authentication. Check the Icom website for details : <http://www.icom.co.jp/world/genuine-info/>



OPTIONS

BATTERY PACKS & CASE

Battery pack type	Capacity	Operating time*
BP-298 Rechargeable Li-ion	2100 mAh (min.) 2250 mAh (typ.)	Up to 19 hours
BP-299 Rechargeable Li-ion	3050 mAh (min.) 3150 mAh (typ.)	Up to 27 hours
BP-264 Rechargeable Ni-MH	1400 mAh	Up to 12.5 hours
BP-263 AA (LR6) batteries × 6	—	—

* EX Hi power. TX : RX : standby = 5 : 5 : 90 (3 sec. : 3 sec. : 54 sec.) (The Power Save function is set to "P-S.16")

RAPID CHARGERS

BC-240 Rapid charger for BP-298/BP-299
BC-191 Rapid charger for BP-264



DESKTOP CHARGER

BC-192 Regular charger for BP-264



MULTI-CHARGER

BC-214N* For BP-298/BP-299



MULTI-CHARGER

BC-197* For BP-264



*The AD-139/AD-120 charger adapters are supplied with the BC-214N/BC-197, depending on the charger version.

SPEAKER-MICROPHONES



EARPHONE-MICROPHONES



HEADSETS

HS-94LWP Ear-hook type with a waterproof connector

HS-95LWP Behind-the-head type with a waterproof connector

HS-97* Throat type

*Either the VS-4LA or OPC-2004LA is required when using the HS-97



PTT SWITCH CABLE & PLUG ADAPTER CABLE

VS-4LA

For manual PTT operation

OPC-2004LA

For VOX operation



CIGARETTE LIGHTER CABLE

CP-23L



DC POWER CABLE

OPC-656



CHARGER BRACKET

MB-130



BELT CLIP

MB-124



ANTENNAS

FA-B45V 144–148 MHz

FA-B57V 160 MHz

FA-B57U 430–450 MHz

FA-B03U 330–380 MHz

PROGRAMMING CABLES

OPC-478UC Handheld to PC USB cable

OPC-474 Handheld to handheld

PROGRAMMING SOFTWARE

CS-V86 Programming software

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. QR Code is registered trademark of DENSO WAVE INCORPORATED in Japan and in other countries. All trademarks are the properties of their respective holders.

Icom Inc. 1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icom.co.jp/world

Count on us!

Icom America Inc.
www.icomamerica.com

Icom (Europe) GmbH
www.icomeurope.com

Icom (Australia) Pty. Ltd.
www.icom.net.au

Your local distributor/dealer:

Icom Canada
www.icomcanada.com

Icom Spain S.L.
www.icomspain.com

Shanghai Icom Ltd.
www.bjicom.com

Icom Brazil
E-mail: sales@icombrasil.com

Icom (UK) Ltd.
www.icomuk.co.uk

Icom France s.a.s.
www.icom-france.com